

## Specification

		4JH4TE			4JH4-HTE			4JH3-DTE	
<b>Class</b>		4JH4-TFE	4JH4-TBE	4JH4-TIE	4JH4-HTFE	4JH4-HTBE	4JH4-HTIE	4JH3-DTHE	4JH3-DTHE1
<b>Configuration</b>		4-stroke, vertical , water cooled - direct injection							
<b>Cylinders</b>		4 in-line			4 in-line			4 in-line	
<b>Maximum Output</b>		75mhp @ 3200rpm			110mhp @ 3200rpm			125mhp @ 3800rpm	
<b>Cooling System</b>		Freshwater cooling by centrifugal freshwater pump and rubber impeller sea water pump							
<b>Bore x Stroke</b>		84 x 90 mm			84 x 90 mm			84 x 90 mm	
<b>Displacement</b>		1.995 litres			1.995 litres			1.995 litres	
<b>Aspiration</b>		Turbocharged			Turbocharged with intercooler				
<b>Dry Weight</b>		235 kg	237 kg	237 kg	245 kg	247 kg	248 kg	260 kg	259 kg
<b>Reduction (FWD) &amp; Model of Gear</b>		ZF30M	KM4A2	ZF25A	ZF30M	KM4A2	ZF25A	KMH4A	ZF25A
		2.15 / 2.70	1.47 / 2.14 / 2.63	2.00 / 2.48	2.15 / 2.70	1.47 / 2.14 / 2.63	2.00 / 2.48	2.04/2.45	2.00 / 2.48
<b>Direction of Rotation</b>	<b>C/S</b>	CCW viewed from stern							
	<b>P/S</b>	CW	Bi Rotation	Bi Rotation	CW	Bi Rotation	Bi Rotation		Bi Rotation